



EV Charger

AC-EVC-020 Local Controller

The FIMER AC-EVC charger line is based on solidity and functionality, in compliance with the international standard IEC 61851-1.

AC-EVC-020 Local Controller is a 2x22kW charging station equipped with RfID local recognition system and auto-programming functions, allowing individual charging and providing efficient security and authorization management.

2x22 kW

The AC-EVC-020 is equipped with:

- Two type 2 sockets, with all the measurement and protection systems, electromechanical retention during charging, communication with the electric vehicle, connection monitoring and regulation of the current through PWM and differential protection circuit breaker type B.
- Color-coded status LED for each socket (ready to use, charging, alarm, etc ...)
- Smart fault management, with automatic reclosure of the circuit breaker.
- Internal load manager for the distribution of the maximum load set by the user, between the two sockets.
- Plug & Charge operation mode.
- Back-up power supply with super “Supercap” capacitors.
- Internal temperature sensors.
- Stainless steel case.
- OLED display with status, kWh counter, instantaneous kW, etc ...
- RFID reader for user authentication and recharge management.
- Charging sockets equipped with protection and safety systems

- Automatic reclosure of the differential breaker
- Shutter-type auto reclosing sockets, vandal-proof
- Internal Load Manager
- External management system - MODBUS TCP/IP

Signaling and control

- Status LEDs and light signaling
- Display OLED 2x22 characters
- Authentication and unlocking systems via RFID

Types of connectors


- Connector Type 2
- IEC/EN 62196-2
- Station fixed socket
- Connector used for AC recharging up to 22kW



2x22 kW

Display
OLED

RFID



Remote

Technical data

Model	AC-EVC-020			
Charging mode / Case	Mode 3, case B ¹⁾			
Type of sockets	Type 2 ²⁾			
Maximum AC power	2x22 kW			
Operating voltage	3x 400V _{AC} +/-10% (50 o 60 Hz)			
Maximum current deliverable	32A			
IP protection class	IP 54			
Casing material	Stainless steel AISI 304			
IK protection class (external impacts)	IK10			
Dimensions	1315x437x293			
Weight	48 Kg			
Environment data				
Operating temperature	-25°C ... 50°C			
Storage temperatures	-25°C ... 70°C			
Humidity	0 % .. 95 % (without condensation)			
Altitude	Up to 2000m			
Type of installation	Suitable also for outdoor installation			
Internal components				
Circuit breaker protection switch	4X D40			
Leakage detect protection	In compliance with IEC 61851, made by RCM (RCD Type B optional)			
Energy Meter	MID certified 3ph + N	3x400/230V kWh Class B ³⁾	kWh Class 1 ⁴⁾ kVar Class 2 ⁵⁾	RS-485 monitor
Contactors	4xNO 40A, AC-1 @40°C		Aux Contact 1xNO + 1xNC	
Plug-socket	PWM-CP, PP ¹⁾			
Electronic control board				
Board power supply voltage	24 V _{DC} ±5%			
Internal diagnostic systems	Measurement of all internal tensions	Monitoring of internal temperatures	Monitoring of the status of the contactor and of the circuit-breaker	Ground fault reclosure system Monitoring of electromechanical component states
Electronic control board	Microprocessor			

1) In compliance with IEC 61851-1.

2) In compliance with IEC 62196-2.

3) In compliance with EN50470-3.

4) In compliance with EN62053-21.

5) In compliance with EN62053-23.

Remark. Features not specifically listed in the present data sheet are not included in the product



For more information please contact your local FIMER representative or visit:

fimer.com

We reserve the right to make technical changes or modify the contents of this document without prior notice. With regard to purchase orders, the agreed particulars shall prevail. FIMER does not accept any responsibility whatsoever for potential errors or possible lack of information in this document.

We reserve all rights in this document and in the subject matter and illustrations contained therein. Any reproduction, disclosure to third parties or utilization of its contents – in whole or in parts – is forbidden without prior written consent of FIMER. Copyright© 2020 FIMER. All rights reserved.

