







# STAR SERIES MONO PERC 120-cell MODULE

## EG-460M60-HLV

### 440~460W


0~3% POSITIVE TOLERANCE

#### KEY FEATURES

- 
**Mbb cell design**  
 Multi Busbar cells brings lower resistance and increased Busbar reflectance ensures higher power output
- 
**High compatibility**  
 Innovative 182mm big cell, small size model design, compatible to variance Roof-top and installation methodology
- 
**High Reliability**  
 Strict in-house testing in PV Lab which is CNAS approved & TUV /VDE certified
- 
**Excellent Low-light Performance**  
 Advanced solar cell and glass surface texturing technology allows for excellent performance in low-light environments
- 
**Highly Mechanical Load Design**  
 Certified to withstand:5400Pa snow load and 2400Pa wind load
- 
**PID Resistant**  
 Excellent PID resistance performance optimized by unique structural design

#### LINEAR PERFORMANCE WARRANTY


 12 Year Product Warranty  25 Year Linear Power Warranty





As a BloombergNEF Tier 1 and global leading manufacturer since 1998, EGING PV is committed to supplying reliable and durable PV products to customers to create together a greener planet.

# EG-460M60-HLV

## Engineering Drawings



## I-V Curves



## Packing Configuration

Pieces per pallet	36
Size of packing (mm)	1940*1135*1255
Weight of packing (kg)	848
Pieces per container	864
Size of container	40'HC

## Electrical Characteristics

Power level	440	445	450	455	460
Pmax (W)	440	445	450	455	460
Vmp (V)	34.71	34.93	35.16	35.39	35.61
Imp (A)	12.68	12.74	12.80	12.86	12.92
Voc (V)	41.51	41.73	41.96	42.19	42.41
Isc (A)	13.43	13.49	13.55	13.61	13.67
Module efficiency (%)	20.32	20.55	20.78	21.01	21.24
Maximum system voltage (V)	1500				
Fuse Rating (A)	25				
Temperature coefficient Pmax (%/°C)	-0.350				
Temperature coefficient Isc (%/°C)	0.05				
Temperature coefficient Voc (%/°C)	-0.275				

STC: Irradiance 1000W/m<sup>2</sup>, module temperature 25°C, AM=1.5

## Working Characteristics

Power level	440	445	450	455	460
Pmax (W)	333	337	341	344	348
Vmp (V)	32.43	32.63	32.85	33.06	33.27
Imp (A)	10.27	10.33	10.38	10.41	10.46
Voc (V)	38.78	38.98	39.20	39.41	39.62
Isc (A)	10.90	10.95	11.00	11.05	11.10
Power tolerance (%)	0~+3				
NOCT (°C)	44 ± 2				

NOCT: Conditions: Irradiance 800W/m<sup>2</sup>, ambient temperature 20°C, wind speed 1m/s

## Mechanical Characteristics

Number of cells	120pcs
Size of cell (mm)	182*91
Type of cell	Mono
Thickness of glass (mm)	3.2
Type of frame	Anodized aluminum alloy
Junction box	IP68
Size of module (mm)	1909*1134*30
Weight (kg)	22.3
Cables/connectors	4mm <sup>2</sup> , MC4 compatible
Length of Cabel	Portrait: +300mm/-300mm

## Maximum Ratings

Operating Temperature(°C)	-40~85
Operating humidity(°C)	5~85
Allowable Hail Load	25mm ice-ball with velocity of 23m/s

Revised in July 2022 1st Edition

CAUTION: All rights reserved by EGING PV.

Specifications included in this datasheet are subject to change without notice.



Tel: 86-519-82585880

Zip: 213213

Add: No.18, Jinwu Road, Jintan Dist,

Changzhou City, Jiangsu Province.

Email: marketing@egingpv.com

Web: www.egingpv.com